

2022 STOCK/WIRE 4 & 6 CYL FWD

BUMPERS

1. Bumpers must remain stock. FACTORY PLASTIC BUMPER COVERS MUST BE REMOVED BEFORE ENTERING VENUE.
2. Bumpers swaps are permitted but must be from another compact style car FROM SAME TIME PERIOD.
3. Bumpers may be welded on WITH NO EXTRA METAL

FUEL AND BATTERIES

1. Factory gas tanks may be left under car if in front of rear wheels.
2. If running factory tank, you must have (2) other forms of safety on it such as 9 wire, chains or ratchet straps.
3. Batteries may be moved inside the car on the passenger side floor.
4. Factory fuel tanks may NOT be used inside the car!!
5. Any leaking fuel cell will be turned away and won't pass inspection until the leak is sealed.

SUSPENSION: REAR/FRONT

1. All suspension components must be stock.
2. No solid suspension or aftermarket parts.

BODY/CAGE

1. Hood must have a 12X12 hole for fire safety.
2. Hood may be chained or wired in up to (6) spots of your choice and may also be chain or wired around the bumper in (2) of those (6) spots.
3. Trunk must be chained or wired in up to (6) spots of your choice.
4. There is to be no flat decking or wedging. Creasing may be done at a minimum.
5. Doors may be chained or wired in up to (6) spots of your choice PER door.
6. Drivers' door may be welded solid and may also have another form of protection.
7. You may run a 4-point cage with a halo bar.
8. Cage material may be no larger than 4X4 or 2X6 ¼ inch channel.
9. Cage material must be no thinner than 1/8 inch and absolutely no perforated tubing.
10. Cage material must be 6 inches off the floor.
11. Sides (door bars) must be no longer than 6 inches past the seat bar.
12. Gas Tank protectors are permitted and must be no larger than 24Lx24Wx20H

13. Tank protectors must be at least 2 inches off the floor and 2 inches away from the speaker deck. (pre ran cars will have exceptions)
14. You must have at least (1) windshield bar at least 1 inch wide running from the cowl area to the roof unless you keep windshield in place.
15. Back window bars are NOT permitted.

TIRES AND WHEELS

1. STOCK DOT TIRES ONLY. MUST HAVE A DOT STAMP.
2. Tires may be doubled or tubed.
3. Stock wheels must be used.
4. Side wall protectors, valve stem protectors, bead locks are NOT permitted.
5. All wheel weights MUST be removed. This is for the safety of fellow drivers, fans and officials.

OFFICIALS DECISION IS FINAL

Questions please contact:

Perry Swab 814-882-4864

Bob Head 716-487-7510

Dakota Papsun 814-720-4611